

WIRELESS EXCELLENCE

Free Space Optics (FSO) Automatic Transmit Power Control (ATPC) Overview



About Wireless Excellence

Founded in 1995 and with headquarters in Oxford UK, Wireless Excellence Limited is a leading designer and supplier of outdoor and indoor Broadband Wireless communication products.

With a complete range of solutions including Radio, Microwave, Millimeter-Wave, Free Space Optics, WiFi and WiMax solutions, customers in over 60 countries have chosen Wireless Excellence as the "one stop shop" solution of choice for dependable wireless networking.

About FSO

FSO Technology leverages Infrared beams for communication purposes, and unlike Fibre based systems, does so wirelessly. Speeds in excess of a Gigabit are readily available and distances of 4km are possible.

Our FSO links have been deployed in over 60 countries including major telecom and corporate networks, and have many advanced features which increase flexibility, reliability, performance, management capability and total-cost-of-ownership.

Summary


Automatic Transmit Power Control (ATPC) is a new product feature available on Wireless Excellence FSO products. The transmitted optical power is automatically adjusted to ensure that the optimum power level is received at the remote terminal. Sophisticated software within each FSO unit continuously monitors remote power levels using the unique Wireless Excellence out-of-band telemetry system, and adjusts power by up to 12dB (16x).

Features

- Adjustment of transmit optical power
- Dynamic range 12dB
- Manual, fixed or Automatic modes
- 0.5dB resolution
- Local and Remote monitoring & control

Benefits

- Improved link margin against poor weather
- Install products at short ranges
- No fixed attenuators required
- Reduces risk of solar outages





Example of poor weather conditions such as fog over a river. ATPC significantly increases link margin and availability.

Comparison of Link Performance with and without ATPC



A brief comparison of FSO with and without ATPC shows a clear advantage to the user.

FSO link with ATPC switched off



These graphs, taken from FSO GraphManager™ management system, show a Wireless Excellence link without ATPC enabled, showing significant variations in received signal level (RSSI). RSSI variations can be caused by weather effects such as fog, heavy rain, snow or dust storms; also thermal effects, bracket movement and long-term drift. Lower RSSI means degraded signal-to-noise-ratio (SNR) at the optical receiver, resulting in degraded Bit-Error-Rate (BER), in severe cases causing packet loss and reduced throughput in data networks.

FSO link with ATPC enabled



A Wireless Excellence FSO Link with ATPC enabled in identical conditions shows almost no variation in received power (RSSI). The controller automatically adjusts the transmitted power levels to ensure optimum signal received at both ends of the link.

Optimum power levels mean minimum Bit-Error-Rate (BER) and reduced risk of receiver overload in adverse east-west locations or unstable mounts.

Operational Description

ATPC is a standard feature of Carrier-class Wireless Excellence FSO products.

A Wireless Excellence FSO Link comprises two FSO units, each transmitting user data and telemetry signals to each other. Each FSO head unit decodes the incoming remote RSSI levels and a sophisticated software algorithm uses these to vary the local transmit laser power. In automatic mode, this is adjusted to maintain an optimum received power level at the remote FSO terminal.

In automatic mode, the local transmit power is regularly updated to avoid either low signal or saturation of the remote optical receiver, which would cause data errors and ultimately link outage. ATPC acts to decrease output power from the nominal 'full power' output of a Wireless Excellence FSO system. This ensures that optical eye safety is not compromised, compliant with Class 1M standards at all power levels; and that the laser device(s) experience lower stress, therefore extending the operational lifetime.

As ATPC does not increase power beyond 'nominal full power', it does not extend the maximum range of each system type; however, it does allow the system to be installed at much shorter distances than without ATPC. Reducing the output power eliminates the requirement for defocusing or attenuation of the link to achieve the optimum RSSI levels.

ATPC gives a Wireless Excellence link a 12dB advantage over non-ATPC systems in poor weather, such as fog; increased atmospheric attenuation is overcome by increasing the optical output power up to the maximum available.

ATPC can also help if the link suffers from interference by the sun; in rare cases where solar energy is incident on the receiver, the laser output power of the opposite unit is reduced to ensure that the combined solar plus FSO power received does not saturate the optical receiver.

ATPC can be controlled by an installer using the Wireless Excellence Alignment Module, and remotely from a workstation or laptop using FSO LinkManager™.

The alignment module incorporates a menu system where the mode of operation can be selected between ATPC mode "off" (maximum power), "manual" (enabling manual control of the local Tx power) or "auto" where the local unit adjusts its output power to maintain the pre-set RSSI value of the remote end.

LinkManager™ provides the same control as the alignment module with the added options of being able to control both the local and remote settings and being able to adjust the pre-set RSSI targets stored in the heads. By this means, ATPC features can be enabled or disabled remotely without need to visit a rooftop location.

ATPC Products

FSO products	CF Access™ CF 622™ CF Gigabit™
Compatibility	-ATPC versions

ATPC Control interfaces

Installation	FSO Alignment Unit™
RS232, 10BaseT Ethernet	FSO LinkManager™

Part Numbers

Product Code	Description
[CF/A/G] xxxx -ATPC	ATPC enhancement for Wireless Excellence FSO systems. Consists as hardware and firmware enhancement to FSO units. Operates with Wireless Excellence Alignment Unit™ and Wireless Excellence LinkManager™

T: +44 (0870) 495 9169
F: +44 (0871) 918 7618
E: sales@wirelessexcellence.com
W: www.wirelessexcellence.com

Wireless Excellence Limited
Sandford Gate
East Point Business Park
Sandy Lane West
Oxford OX4 6LB